

OIL MUD TEST KIT

PORTA LAB™ MODEL 866



Oil Mud Testing Kit

Order No. 210412

The Fann Oil Mud Test Kit is designed as a complement to the Basic Mud Testing Kit by providing all necessary drilling fluid testing equipment required for field testing of oil based drilling fluids according to **API Recommended Practice 13B-2**. All testing apparatus and reagents are contained in a specially designed stainless steel case.

Note: the Electrical Stability Tester is contained in a separate high-impact plastic carrying case to protect delicate electronics.

Specifications:

Dimensions 26 X 9 X 12 inches
Weight 55 pounds

Oil Mud Kit includes the following components:

Description	Part No.
<i>Rheometer, Hand Crank</i>	206984
<i>Cup-Heater for Rheometer</i>	206961
<i>Retort, 10ml</i>	210485
<i>Mixer, 115VAC w/Cup</i>	205986
<i>Digital Thermometer with Probe</i>	206044
<i>Electrical Stability Tester</i>	102130986
<i>Sand Content Tube</i>	209663
<i>Graduated Cylinder, 50ml</i>	205867
<i>Graduated Cylinder, 10ml (2)</i>	205869
<i>Syringe 2cc</i>	205891
<i>Syringe 10cc</i>	205896
<i>Erlenmeyer Flask, 250ml</i>	205914
<i>Pipette 1ml</i>	206026
<i>Pipette 5ml</i>	206028
<i>Pipette 10ml</i>	206029
<i>Brush Large</i>	205852
<i>Brush Medium</i>	205853
<i>Titration Dish</i>	205902
<i>Test Tube</i>	205234
<i>Dial thermometer, 50-350°F</i>	206038
<i>Pocket thermometer, 0-220°F</i>	206568
<i>Hardness Indicator</i>	209821
<i>Hardness Buffer</i>	209822
<i>Hardness Titrant, 400mg/L</i>	209828
<i>Potassium Chromate</i>	209850
<i>Phenolphthalein Indicator</i>	209855
<i>Sulfuric Acid</i>	209871
<i>Sodium Hydroxide</i>	209906
<i>Silver Nitrate, .282N</i>	209922
<i>Wetting Agent</i>	209938
<i>Distilled Water</i>	209943
<i>Normal Propoxy Propanol</i>	209954
<i>Aquatone-S Solution</i>	209957
<i>Aniline, Reagent Grade</i>	210154
<i>Bara Klean</i>	209951

Fann offers a complete line of instrumentation for testing all types of drilling fluids in accordance with API Recommended Procedures